




## Rock Steady GoPro Slim Surface Mount

FF-SLMTS



0649870157072

Includes:  
Surface plate  
(2) centering washers  
(2) #8 and #10 screws  
Rubber gasket  
GoPro Slim adapter



### **MUST READ BEFORE USE**

BY USING THIS PRODUCT YOU ARE AGREEING TO HAVE READ AND UNDERSTAND THE FOLLOWING:

IT IS THE RESPONSIBILITY OF THE END USER OF THIS PRODUCT TO CONSIDER ANY SAFETY PRECAUTIONS NECESSARY (SUCH AS SAFETY WIRE OR LOCTITE) TO ELLIMNATE ANY POSSIBILITY OF FAILURE OR DETACHMENT. IT IS THE RESPOSIBILITY OF THE END USER TO VERIFY THIS PRODUCT IS NOT USED IN A MANOR THAT COULD VIOLATE ANY REGULATIONS, HARM PERSONS OR PROPERTY, OR BECOME A DISTRACTION TO THE OPERATOR. THE FAA DOES NOT SUPPORT INSTALLATIONS THAT ARE NOT APPROVED. IT IS THE RESPOSIBILITY OF THE END USER TO VERIFY THIS PRODUCT IS USED IN A MANOR COMLIANT WITH FEDERAL AVIATION REGULATIONS.

THIS PRODUCT IS PROVIDED AS IS WITHOUT ANY GUARANTEES OR WARRANTY. IN ASSOCIATION WITH THE PRODUCT, FLIGHT FLIX, LLC MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OF TITLE, OR OF NONINFRINGEMENT OF THIRD PARTY RIGHTS. USE OF THE PRODUCT BY A USER IS AT THE USER'S RISKNO ADVICE OR INFORMATION, WHETHER ORAL OR WRITTEN, OBTAINED FROM **FLIGHT FLIX LLC** OR THROUGH THE SERVICE OR CONTENT, WILL CREATE ANY WARRANTY NOT EXPRESSLY MADE HEREIN. YOU ARE SOLELY RESPONSIBLE FOR ALL OF YOUR COMMUNICATIONS AND INTERACTIONS WITH OTHER USERS OF THE PRODUCT AND WITH OTHER PERSONS WITH WHOM YOU COMMUNICATE OR INTERACT AS A RESULT OF YOUR



Take the Slim GoPro adapter and thread the jamb nut towards the adapter side of the stud.



Thread the adapter 3 to 4 full turns into the base. Align the adapter in the desired direction the camera should face.




Use a 7/16" wrench to tighten the jamb nut.



Remove two fasteners spaced between 2" to 5" apart on your mounting surface. Place the rubber gasket under the surface mount.



Use the centering washers and fasteners to attach the mount. Longer screws may be needed. It is recommended to only use holes with nutplates.



Use safety wire, loctite, or nylock hardware as necessary for security.